

1

5

10

15

20

25

P E T I T I O N

Commissioner for Patents
Alexandria, VA 22313

Your Petitioner, ARNOLD G. LEGBAND, a citizen of the United States and a resident of the State of Nebraska, whose post office address is P.O. Box 1525, Fremont, Nebraska 68025, prays that Letters Patent may be granted to him for a

BRACKET FOR USE IN REPANELING A STRUCTURE

as set forth in the following specification.

BACKGROUND OF THE INVENTION

The present invention relates to building materials and more particularly to an elongated bracket that is used in retrofitting new building panels to existing structures with minimal labor and additional materials.

DESCRIPTION OF THE PRIOR ART

Lightweight steel-framed structures typically employ ribbed building panels to cover the roof and walls of the structure. Oftentimes, the building panels are constructed from metal, such as steel or aluminum. The building panels are formed to have a rib and valley profile to strengthen the building panels despite their thin construction.

Over time, due to natural deterioration or damage from various causes, the building panels on structures need to be replaced. However, the removal and replacement of the building panels consumes a great deal of labor and financial resources. Oftentimes, the best solution to the repair of a structure having

1 deteriorating or damaged building panels is to simply retrofit the structure with new
roof or wall panels by directly securing the new building panels to the existing
building panels. In this manner, the labor and expense of removing the existing
5 building panels can be saved.

A number of concerns arise when retrofitting a structure with new building
panels. First, the spacing between the new and existing building panels must be
taken into consideration. Second, the ability for wind to flow beneath the new
building panels, causing a sail-like effect, must be considered for its potential for
10 property damage and injury. Finally, the manner in which the new building panels
are coupled to the structure must be carefully considered. As the new and existing
body panels are subjected to a range of temperatures, their rates of expansion and
contraction may differ to a varying degree. Moreover, the more complex retrofitting
the structure becomes, the cost/benefit ratio of the retrofitting the structure as
15 compared to replacing the building panels decreases.

One example of a system for retrofitting a structure with new building panels
is taught by U.S. Patent No. 5,367,848. The system is essentially provided with an
elongated bracket having a Z-shaped cross-section. The bracket is designed to
20 extend transversely across the existing building panels adjacent the location of a
frame member. A series of notches are formed within the one generally vertical wall
member of the Z-shaped bracket to allow the bracket to "nest" onto and over the
ribbed profile of the existing building panel. A bottom wall portion extends outwardly
25

1 from the bracket and is provided with apertures so that the user may secure the
bracket to the existing building panel and the frame member using a plurality of new
fasteners. A top wall member provides a mating surface for supporting the new
5 building panel. A second series of new fasteners are used to secure the new
building panel to the bracket. While the design of the bracket solved a number of
problems existing in the art at the time it was introduced, it still suffers from a
number of deficiencies. First, the goal in retrofitting building panels is to reduce the
overall labor and materials required to retrofit the new building panels onto the
10 structure. The design of the Z-shaped bracket requires a first course of fasteners to
secure the bracket to the existing building panel and frame member. Then, a
second course of fasteners is required to secure the new building panel to the
bracket. An additional deficiency with the bracket stems from its Z-shaped design.
15 The bottom wall member is secured to the existing building panel and the frame
member, and the new building panel is fastened only to the top wall member of the
bracket. Accordingly, there is no direct structural connection between the new
building panel and the frame member of the building. The strength of the
connection between the new building panel and the building itself depends upon the
20 strength of the bracket. Moreover, the Z shape provides only one vertically-oriented
wall member, which provides a less than desirable level of stability when forces are
exerted on the new building panels.

1 Accordingly, what is needed is a new system and method for retrofitting
building panels to a structure that not only provides a convenient manner of
retrofitting building panels but also decreases the labor and materials required to
5 implement the system while increasing the overall stability of the new building
panels with respect to the structure.

SUMMARY OF THE INVENTION

10 The novel bracket of the present invention is provided for use in retrofitting
new building panels to a structure having existing building panels that are fastened
to frame members. The bracket is generally provided with a forward wall and a
rearward wall that are coupled to one another at their upper end portions by a top
wall. The interconnection between the forward, rearward and top walls defines a
channel that extends along the length of the bracket. Accordingly, in one preferred
15 embodiment, the bracket is generally U-shaped.

The bottom end portions of the forward and rearward walls are selectively
shaped to mimic the rib and valley profile of the existing building panels, permitting
the bracket to substantially engage its lower end portion with the upper surface of
the existing building panel. The channel is shaped and sized to substantially
20 enclose the existing fasteners, which couple the existing building panel to the frame
member. Accordingly, a single elongated bracket may be positioned to enclose a
transverse line of fasteners across the existing building panel, preventing the
bracket from sliding forward or rearward with respect to the existing building panel.

1 A single course of fasteners are then used to secure the new building panel to the
bracket and the existing building panel. In a preferred embodiment, the fasteners
will also engage the frame member.

5 It is therefore one of the principal objects of the present invention to provide a
bracket for retrofitting new building panels to a structure with a minimal amount of
materials and labor.

A further object of the present invention is to provide a bracket for retrofitting
building panels to a structure that can be adapted for use with existing building
10 panels having nearly any profile.

Yet another object of the present invention is to provide a bracket that
reduces the typical number of steps required for retrofitting building panels to a
structure.

15 A further object of the present invention is to provide a bracket that provides a
stable mounting structure for new building panels that does not require a separate
fastener means to couple the bracket to the existing building panel prior to the
installation of the new building panel.

20 Still another object of the present invention is to provide a bracket for
retrofitting new building panels to a structure that is fabricated from a generally
insulative material.

Yet another object of the present invention is to provide a bracket for
retrofitting new building panels to a structure that is relatively simple in construction.

25

1 These and other objects of the present invention will be clear to those of skill
in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is a perspective view of one embodiment of the bracket of the
present invention as the same might be used to secure a new roof panel to an
existing roof panel on a structure;

 Figure 2 is an isometric view of one embodiment of the bracket of the present
invention;

10 Figure 3 is an isometric view of the bracket depicted in Figure 1; and

 Figure 4 is a partial side elevation view depicting one manner in which the
bracket of the present invention could be used to secure a new roof panel to an
existing roof panel on a structure.

15 DESCRIPTION OF THE PREFERRED EMBODIMENT

 The bracket 10 of the present invention is generally depicted in Figures 1-4 in
some of its possible embodiments. Generally, the bracket 10 is provided with a
forward wall 12, rearward wall 14 and a top wall 16. The forward wall 12, rearward
wall 14 and top wall 16 are coupled to one another so that they define a channel 18
20 that extends along the length of the bracket 10.

 Although it is contemplated that the bracket 10 could be fabricated from
nearly any material, including the various types of metals from which building panels
are fabricated, it is preferred that the channel 10 be constructed from a generally

1 insulative material such as plastic, fiberglass-reinforced plastic and the like. The
insulative property will provide a benefit to the finished, retrofit building panels where
differing rates of expansion and contraction between the new and existing panels is
a concern. Moreover, the transmission of thermal energy will be greatly reduced.
5 Finally, such insulative materials are easily fabricated into one of any number of
shapes and sizes, depending on the particular system requirements. For example,
in a preferred embodiment, the lower end portions of the forward wall 12 and the
rearward wall 14 may be shaped to have a profile that mimics a profile of the rib
10 portions 20 and valley portions 22 of the existing building panels 24, as depicted in
Figure 1.

The profile of the lower end portions of the forward wall 12 and the rearward
wall 14 can be cast into molds when the bracket 10 is fabricated or shaped after the
15 fabrication process, where either molded or non-molded materials are used.
However, it is preferred that the bracket 10 be constructed such that minor
alterations may be performed on the job site with a simple hand tool to marry the
profile of the bracket 10 to the profile of the existing building panel 24. The bracket
10 may also be originally formed as a "blank" 26 to be shaped with a profile at a
20 later time depending on the particular circumstances of the retrofitting job. The
blank 26, shown in Figure 2, may also be used where close conformity to the profile
of the existing building panels is not necessary or desirable.

1 In a preferred embodiment, the channel 18 should be sized and shaped to
substantially enclose one or more of the existing fasteners 28, which secure the
existing building panels 24 to the frame member or purlin 30 of the structure.
Typically, a plurality of existing fasteners 28 will be disposed within the existing
5 building panel 24 in a generally straight, transverse line which indicates the location
of the frame member 30 beneath the existing building panel 24. Substantially
enclosing the line of fasteners 28 within the channel 18 provides a number of
benefits. One such benefit is that the lower end portions of the forward wall 12 and
10 the rearward wall 14 will tend to engage the head portion of the existing fasteners
28, thus preventing the lateral, parallel movement of the bracket 10 with respect to
the existing building panel 24.

 In use, the bracket 10 is simply positioned so that the profile of the lower end
15 portion of the forward wall 12 and the rearward wall 14 align with the profile of the
existing building panel 24. The bracket 10 can then be placed against the existing
building panel 24 so that the existing fasteners 28 are enclosed within the channel
18. A new building panel 32 may then be placed into position against the top wall
16 of the bracket 10. As can be seen in Figures 1 and 4, the height of the bracket
20 10 defines the spaced relationship between the existing building panel 24 and the
new building panel 32. Therefore, where a larger or smaller distance between the
two building panels is desired, the height of the bracket 10 should be fabricated or
adjusted accordingly. This may become particularly relevant where an insulative
25

1 material is to be disposed between the existing building panel 24 and the new
building panel 32. The insulative material may be one of several known insulative
materials used generally in the construction industry and should be selected based
5 upon the particular insulating and environmental conditions present for the given job
site. The distance between the existing building panel 24 and the new building
panel 32 will also become a consideration where the lifting and flexing effects of
wind on the building panels is a concern.

10 Once the new building panels 32 are in position atop the top wall 16 of the
bracket 10, new fasteners 34 can be disposed through the new building panel 32
and into the bracket 10, existing building panel 24, and preferably the frame
member 30 as well. However, it is contemplated that in certain applications, the
new building panel 32 may be secured by engaging the fastener 34 with only the
15 bracket 10 and the existing building panel 24. The fastener 34 depicted in Figure 4
is shown to be a bolt and nut. However, standard roofing fasteners, self-tapping
screws and the like may all be used, depending on the particular circumstances.

20 The forward wall 12 and rearward wall 14 are depicted in Figure 4 as being
generally parallel with one another and spaced apart by the top wall 16. However,
variations to this U shape are contemplated. For example, the forward wall 12 and
rearward wall 14 may be angled inwardly or outwardly somewhat. Moreover, the
size and length of the top wall 16 may be varied to provide a larger or smaller
25 surface upon which the new building panel 32 will rest. Accordingly, a V shape, C

1 shape and other geometries are contemplated. However, it is preferred that the
forward wall 12 and rearward wall 14 be of generally equal length and in a spaced-
apart relationship so that a forward and rearward footing is provided for stability.
Accordingly, additional resistance to the forward or rearward tipping or flexing of the
5 new building panel 32 is provided. The stability of the new building panel 32 is
amplified when used with the bracket 10 and coupled to the frame member 30, as
depicted in Figure 4. In this manner, the stability of the structure is enhanced by the
shape of the bracket 10 but not solely dependent thereon.

10 In the drawings and in the specification, there have been set forth preferred
embodiments of the invention; and although specific items are employed, these are
used in a generic and descriptive sense only and not for purposes of limitation.
Changes in the form and proportion of parts, as well as substitution of equivalents,
15 are contemplated as circumstances may suggest or render expedient without
departing from the spirit or scope of the invention as further defined in the following
claims.

20 Thus it can be seen that the invention accomplishes at least all of its stated
objectives.